Kidde ECS™ Fire Suppression System Component Description




180 Degree Pendant Nozzle


Effective: March 2018 K-90-2150 Rev BB


FEATURES

- For Use with UL Listed, ULC Listed & FMRC Approved Systems
- RoHS Compliant

P/N: 90-19401X-XXX







LABEL DETAIL

Pipe Size	Α	В	С	D
1/2" (12.20 mm)	1.25" (31.75 mm)	1.250" (31.75 mm)	1.687" (42.84 mm)	2.000" (50.80 mm)
3/4" (19.05 mm)	1.50" (38.10 mm)	1.375" (34.92 mm)	1.950" (48.89 mm)	2.296" (58.31 mm)
1" (25.40 mm)	1.75" (44.45 mm)	1.562" (39.67 mm)	2.218" (56.33 mm)	2.671" (67.84 mm)
1¼"(31.75 mm)	2.25" (57.15 mm)	1.750" (44.45 mm)	2.656" (67.46 mm)	3.250" (82.55 mm)
1½" (38.10 mm)	2.50" (63.50 mm)	1.950" (48.89 mm)	2.950" (74.93 mm)	3.625" (92.07 mm)
2" (50.80 mm)	3.00" (76.2 mm)	1.968" (49.98 mm)	2.875" (73.02 mm)	3.656" (92.86 mm)

Note: A selection of orifices are available for each nozzle size. Consult your Kidde Design and Installation Manual for details.

COMPATIBILITY

Series	For Use With
Kidde ECS HFC-227ea	Х

This literature is provided for informational purposes only. KIDDE-FENWAL, INC. believes this data to be accurate, but it is published and presented without any guarantee or warranty whatsoever. KIDDE-FENWAL, INC. assumes no responsibility for the product's suitability for a particular application. The fire suppression system design, installation, maintenance, service and troubleshooting must be performed by trained, authorized Kidde Fire Systems distributors for the product to work correctly. If you need more information on this product, or if you have a particular problem or question, contact KIDDE-FENWAL, INC., Ashland, MA 01721 USA. Telephone: (508) 881-2000.

EXPORT INFORMATION (USA)

Jurisdiction: EAR
Classification: EAR99

This document contains technical data subject to the EAR.

All trademarks are the property of their respective owners. ©2018 Kidde-Fenwal, Inc.

Kidde Fire Systems 400 Main Street Ashland, MA 01721 Ph: 508.881.2000 Fax: 508.881.8920 www.kiddefiresystems.com