

# Component Description

## Cable, 1/16" Steel P/N 06-118316-100 and WK-219649-000

Effective: August 2016  
K-85-4000 Rev AA

### FEATURES

- *UL Listed, ULC Listed, and FM Approved for use with systems listed in the Compatibility table.*
- *REACH and RoHS compliant*
- *Used for Remote Cable Actuation*

### SPECIFICATIONS

Material: Steel

- Corrosion Resisting
- Flexible
- Pre-formed

Nominal Cable Diameter: 1/16 in.

Break Strength: 480 lbs min.

Weight per 100 ft: approx. .75 lbs



### ORDER INFORMATION

Part Number	Length
06-118316-100	100 feet
WK-219649-000	500 feet

### COMPATIBILITY

Series	For Use With	Land DIOM Manual P/N	Marine DIOM Manual P/N
Kidde ECS with HFC-227ea Agent	X	06-236115-001	06-236225-001
Kidde Advanced Delivery with FM-200 <sup>®</sup> Agent	X	06-235068-001	06-236595-001
Kidde ECS with 3M <sup>™</sup> Novec <sup>™</sup> 1230 Fire Protection Fluid	X	06-236553-001	06-236559-001
Kidde Advanced Delivery with 3M <sup>™</sup> Novec <sup>™</sup> 1230 Fire Protection Fluid	X	06-237256-001	06-237257-001

All trademarks are the property of their respective owners.

This literature is provided for informational purposes only. Kidde-Fenwal, Inc. assumes no responsibility for the product's suitability for a particular application. The product must be properly applied to work correctly. The technical data contained herein is limited strictly for informational purposes only. Kidde-Fenwal, Inc. believes this data to be accurate, but it is published and presented without any guarantee or warranty whatsoever. If you need more information on this product, or if you have a particular problem or question, contact Kidde-Fenwal, Inc.

©2016 Kidde-Fenwal, Inc.

**EXPORT INFORMATION (USA)**  
Jurisdiction: EAR  
Classification: EAR99  
This document contains technical data subject to the EAR.

Kidde Fire Systems  
400 Main Street  
Ashland, MA 01721 USA  
Ph: 508.881.2000  
Fax: 508.881.8920  
[www.kiddefiresystems.com](http://www.kiddefiresystems.com)