

# Component Description

## Stackable Electric Control Head Kit with Control Head Monitor and Lever Operated Control Head Data Sheet

Effective: January 2018  
K-85-3002 Rev AB

### FEATURES


- UL Listed, ULC Listed, and FM Approved for use with systems listed below in the Table, "COMPATIBILITY", on page 2.

P/N: 85-486500-010

### ORDER INFORMATION

Part Number	Description
85-486500-010	Kit, Includes: <ul style="list-style-type: none"> <li>• Electrical Control Head, 24 VDC, Stackable, (Ex. Proof), P/N: 82-486500-010</li> <li>• Control Head Monitor, P/N 85-100000-100 (for more information, see data sheet K-85-3000)</li> <li>• Lever Operated Control Head, P/N WK-870652-000 (for more information, see data sheet K-85-6005)</li> </ul>

ELECTRIC CONTROL HEAD, PART NO. 486500-01 IS RATED FOR USE IN HAZARDOUS (CLASSIFIED) LOCATIONS CLASS 1, DIV. I, GROUPS C, D AND CLASS II, DIV. II, GROUPS E, F, G BETWEEN -40F AND 140F. USE CONDUIT SEAL WITHIN 18 IN. (45cm) OF THIS DEVICE.



**Note:** This control head is polarized. Improper wiring will result in failure of this device to operate.



**WARNING**

Electric control head, P/N: 82-486500-010, is designed for installation directly on 487 Series Halon and Kidde ECS agent valves only to a maximum size of 350 lbs. This control head must not be installed on any other type of halon or agent cylinder valve, nitrogen valve, carbon dioxide cylinder valve, FE-13 cylinder valve or Stop (Directional) valve. Installation of this control head to any other device (e.g., pressure operated control head) will result in failure of device to operate.

### MATERIAL

Body: Brass

### SPECIFICATIONS

Voltage: 24 VDC




Figure 1. Electric Control Head (Stackable Type) with Lever Operated Control Head and Control Head Monitor

**COMPATIBILITY**

Series	DIOM P/N	Supplement P/N
Kidde ECS 500 psi with FK-5-1-12 Agent	06-237585-001	N/A
Kidde ECS with 3M™ Novec™ 1230 Fire Protection Fluid*	06-236553-001	N/A
Kidde ECS with HFC-227ea Agent*	06-236115-001	06-236115-003
Kidde Modular ECS with HFC-227ea Agent*	06-236116-001	06-236116-002
*For Cylinders up to 350 lbs. maximum		
<b>Note:</b> Agency listings also apply to the Fenwal Engineered Fire Suppression Systems, when the Control Head Monitor is used on these legacy product lines.		

**EXPORT INFORMATION (USA)**

Jurisdiction: EAR  
 Classification: EAR99  
 This document contains technical data subject to the EAR.

All trademarks are the property of their respective owners.

This literature is provided for informational purposes only. KIDDE-FENWAL, INC. believes this data to be accurate, but it is published and presented without any guarantee or warranty whatsoever. KIDDE-FENWAL, INC. assumes no responsibility for the product's suitability for a particular application. The fire suppression system design, installation, maintenance, service and troubleshooting must be performed by trained, authorized Kidde Fire Systems distributors for the product to work correctly. If you need more information on this product, or if you have a particular problem or question, contact: KIDDE-FENWAL, INC., Ashland, MA 01721 USA, Telephone: (508) 881-2000.

