

# Kidde ECS 500 psi with FK-5-1-12 Fire Protection Fluid



Effective: January 2018  
K-45-0514 Rev AA

## Supervisory Pressure Switch Data Sheet

### FEATURES

- Both Normally Open and Normally Closed Configuration with One Unit
- Suitable for 10 lb. through 1100 lb. Kidde ECS 500 psi Systems cylinders
- UL Listed, ULC Listed, and FM Approved for use with Kidde ECS 500 psi Systems

P/N: 45-118500-001 and 45-500537-001

### DESCRIPTION

The cylinder supervisory pressure switch is intended to detect a fall in pressure in the Kidde ECS 500 psi System cylinder. The cylinder supervisory pressure switch can be wired for either normally open or normally closed operation, depending on installation requirements. This cylinder supervisory pressure switch can be installed on Kidde ECS 500 psi System cylinders, 10 lb. through 1100 lb. size.

### OPERATION

When the pressure in the Kidde ECS 500 psi System container drops from the standard charge pressure of 500 PSI (35 bar) to below 435 PSI (30 bar) the switch operates. If wired in the NC (open-under-pressure) configuration the resulting pressure drop will cause the contacts to close. When connected to a monitored circuit of a suppression control panel the switching will result in an alarm or trouble condition.

### INSTALLATION

The supervisory pressure switch can be installed on a fully charged cylinder, without loss of pressure, provided the unit is handled with care and only by trained service personnel. Remove the protective cap from the pressure connection. Do not apply thread compound to the threads. Install the switch with an 1-1/16 inch open-ended wrench while holding the pressure connection with a 7/16 inch open-end wrench. Tighten hand-tight, plus one-quarter turn. Leak check using a leak detector or bubbling solution. Secure switch body with wrench when connecting electrical conduit.

Isolate the assembly from shock, vibration and areas subject to wide-ranging or rapid temperature fluctuations. Disconnect all supply circuits before wiring the supervisory switch.



### ORDER INFORMATION

The cylinder supervisory pressure switch offers combined normally opened and normally closed functionally. The part number for ordering the cylinder supervisory pressure switch is 45-118500-001 or 45-500537-001 (FOR ATEX VERSION).

### SPECIFICATIONS

Setting:	435 PSI (30 bar) on falling pressure
Electrical rating:	5 Amps, 250 Vac
Wire color coding:	Blue = Normally Open Black = Normally Closed Violet = Common
Operating temperature range:	32 to 130°F (0 to 54°C)
Pressure connection:	0.25 in. SAE 45° flare female with valve core deflector
Wetted materials:	EPR, Brass Copper
Lead length:	36 in. ± 2 in. (914 mm ± 50 mm)

### EXPORT INFORMATION (USA)

Jurisdiction: EAR  
Classification: EAR99  
This document contains technical data subject to the EAR.  
All trademarks are the property of their respective owners.  
©2018 Kidde-Fenwal, Inc.

This literature is provided for informational purposes only. KIDDE-FENWAL, INC. believes this data to be accurate, but it is published and presented without any guarantee or warranty whatsoever. KIDDE-FENWAL, INC. assumes no responsibility for the product's suitability for a particular application. The fire suppression system design, installation, maintenance, service and troubleshooting must be performed by trained, authorized Kidde Fire Systems distributors for the product to work correctly. If you need more information on this product, or if you have a particular problem or question, contact KIDDE-FENWAL, INC., Ashland, MA 01721 USA. Telephone: (508) 881-2000.

Kidde Fire Systems  
400 Main Street  
Ashland, MA 01721  
Ph: 508.881.2000  
Fax: 508.881.8920  
[www.kiddefiresystems.com](http://www.kiddefiresystems.com)